



13038 COLOR COAT FLATTENER

TECHNICAL DATA SHEET

Description

13038 COLOR COAT FLATTENER is an additive used to reduce gloss in all **COLOR COAT** intermix formulas. **13038** will give the user more versatility when matching low gloss OEM colors when using **COLOR COAT** over vinyl and plastic.

Features

- Easily reproduce low gloss OEM appearance
- Increases versatility of **COLOR COAT**
- Works with all **COLOR COAT** formulas
- Simple to use

Typical Properties

Container	Pint
Material VOC	5.94 #/gl (713.1 g/l)
Coating VOC	5.99 #/gl (718.4 g/l)
Volatile Wt %	74.8
Density	8.06 #/gl (968 g/l)

Please refer to www.semproducts.com for physical properties and VOC information. Use VOC calculator to determine VOC of mixtures.

Handling and Application

PREPARATION: Prepare surface according to **COLOR COAT** technical data sheet, **CC TDS**.



MIXING: Shake well. For best results, use only when can temperature is approximately 70°F (21°C).



DO NOT THIN. **13038** is ready to use.

Mix **COLOR COAT** toners without **1300() HIGH GLOSS CLEAR** or **1301() SATIN GLOSS CLEAR** and add **13038** until desired gloss is achieved.

Formulas that have **1302() LOW LUSTER CLEAR** have been formulated to match the OEM gloss level and typically, will not require the use of **13038**.

NOTE: Do not exceed a 10% addition of **13038**. In general, a 10% addition will result in a 25-50% reduction in gloss, depending on the formula and substrate. Hiding and color match may be affected with higher levels of flattener. Always apply product to a test panel before use.

APPLICATION: Apply according to **COLOR COAT** technical data sheet, **CC TDS**.



STORAGE: **13038 COLOR COAT FLATTENER** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **13038** is 5 years when stored under normal conditions.



TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.