



36012 SCRATCH PATCH™

TECHNICAL DATA SHEET

Description

36012 SCRATCH PATCH is a black, solid paint stick that is great for quickly repairing small to medium sized scratches on automotive, marine and industrial type finishes. The air activated formulation and no-drip applicator makes **36012** a must have for touching up sprayed on truckbed liners, bumpers and blacked out accessories.

Features

- Easy to use applicator doesn't drip or leak
- Anti-rust agents fill and seal damaged finishes
- Great for automotive, marine or industrial use
- Excellent for repairing scuffs and scratches in sprayed on truckbed liners
- May be polished to enhance repair

Typical Properties

Container	Crayon applicator
Color	Black
VOC*	3.8 #/g1 (461 g/l)
Dry to touch	1-2 minutes @ 70°F (21°C)
Time to polish	10-15 minutes @ 70°F (21°C)

***For California: Please consult with local regulatory agencies to determine any distribution or application restrictions for 36012.**

Handling and Application

PREPARATION: Clean surface thoroughly with **3837() SEM SOLVE** or **38381 WORLD CLASS™ SURFACE CLEANER**.



APPLICATION:



- For best results, apply on a cool surface out of direct sunlight.
1. Rub paint into scratch with a single application. Deep scratches may require repeat applications. Allow 10 minutes of drying time between coats.
 2. Wipe away excess and allow product to dry.
 3. Repaired area may be lightly polished to restore smooth finish.
 4. Replace cap after use and store in a cool place.

NOTE: To expose additional product, slowly push from bottom. Briefly warm the tube under hot water if product does not push out easily. Do not expose coating to water.

CLEANUP:

Use appropriate cleaning materials compliant with VOC regulations in your area.



STORAGE:



36012 SCRATCH PATCH should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **36012** is 1 year when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.