



# 7770( ) XXX FINISH STRIPPER

## TECHNICAL DATA SHEET

### Description

**7770( ) XXX FINISH STRIPPER** is an aircraft grade, nonflammable remover designed to quickly strip the toughest automotive coatings and adhesives from metal surfaces. The heavy-bodied formula clings to vertical surfaces and is safe for all types of automotive metal.

### Features

- Aircraft grade
- Excellent vertical hold
- Easy clean up
- Nonflammable

### Typical Properties

Containers	<b>77701</b> gallon, <b>77704</b> quart and <b>77703</b> aerosol
Active ingredients	Methylene Chloride and Methanol
Viscosity	2900 cps.
Density	10.00 #/gl (1200 g/l)
Flash point	None
VOC of <b>7770( )</b>	0.91 #/gl (110 g/l)
VOC of <b>77703</b> less exempts	1.84 #/gl (221 g/l)
Vapor pressure of VOC	23 mm Hg @ 20°C
Coverage	100 sq.ft./gl

### Handling and Application

#### PREPARATION:



Use only in well ventilated areas. If possible, use outdoors. Use solvent resistant gloves and safety goggles. For optimal results, use when the temperature is between 65-85°F (18-29°C). Please refer to the MSDS for additional safety information.

#### APPLICATION:



1. Open can slowly to release pressure.
2. Pour a thick coat onto the surface to be stripped and spread with a chemical resistant brush. If using **77703**, spray liberally onto area to be stripped.
3. Depending on the degree of removal, allow **7770( )** to work for 10-20 minutes. Some jobs may require more time, so test a small area before removing **7770( )**.
4. Once the paint is loose, remove the old finish with a flat metal scraper.

**NOTE:** If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

**NOTE:** After each use, turn can upside down and spray several seconds to clear spray tip.

**NOTE: DO NOT USE 7770( )** on plastic, fiberglass, rubber, fabrics or any other synthetic material.

**CLEANUP:**



Dispose of stripped paint in accordance with local EPA guidelines. Clean the entire area with **38373 SEM SOLVE** and allow to dry before applying new refinish system. Please refer to the MSDS for additional cleanup information.

**STORAGE:**



**7770( ) XXX FINISH STRIPPER** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. Exposure to high temperatures will cause the can to swell. **DO NOT** store **7770( )** in basements or other unventilated areas. **KEEP AWAY FROM HEAT AND FLAMES.** Vapors flow along floors, under doors and upon contact with flames or hot surfaces, may produce a toxic poisonous gas and destroy metals. The shelf life for **7770( )** is 1 year when stored under normal conditions.

**TECHNICAL CONSULTATION SERVICE**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

**DISCLAIMER:** The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

**SEM Products, Inc.**  
**1685 Overview Dr. Rock Hill SC 29730**  
**Tel: 800/ 831-1122**  
**[www.semproducts.com](http://www.semproducts.com)**