



77713 XXX BUMPER STRIPPER

TECHNICAL DATA SHEET

Description

77713 XXX BUMPER STRIPPER is a unique formulation that will not swell or attack most urethanes. The heavy bodied consistency clings to the surface of the bumper without sagging and is designed to remove all refinish material.

Features

- Safe for most bumpers
- Convenient aerosol packaging
- Non sag formula

Typical Properties

Container	Aerosol
Active ingredients	Methylene Chloride
VOC	2.31 #/gl (277.0 g/l)

Handling and Application

PREPARATION: Protect nearby areas from overspray. Use only in well ventilated areas. Always wear proper personal protective equipment including solvent resistant gloves, safety goggles and respirator.



APPLICATION:



77713 is designed to remove aftermarket coatings. Repeated applications of **77713** in an attempt to remove the OEM baked finish can cause swelling and distortion of the bumper. Test a small inconspicuous area first before proceeding with the entire job.

Spray on liberally and allow **77713** to work no longer than 10-15 minutes. Neutralize promptly. Some older urethanes may swell, but will return to original contour within 24 hours. **77713** should not be used on Xenoy, PC, ABS, PVC, fiberglass or SMC. Do not use in direct sunlight, spray on hot surfaces or use in windy areas.

When the paint wrinkles or softens, remove with squeegee, steel wool or rags. The surface may be cleaned with **38373 SEM SOLVE** or by washing with water. Allow surface to dry before applying refinish system.

NOTE: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

NOTE: After each use, turn can upside down and spray several seconds to clear spray tip.

CLEAN UP:



Dispose of stripped paint in accordance with local EPA guidelines. Please refer to the MSDS for additional cleanup information.

STORAGE:



77713 XXX BUMPER STRIPPER should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **77713** is 2 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
1685 Overview Dr. Rock Hill 29730
Tel: 800/ 831-1122
www.semproducts.com