



# PROMAX™ XRP

## TECHNICAL DATA SHEET

---

### *Description*

**PROMAX XRP** is a multi-purpose enamel for direct use on metal, wood and fiberglass. In addition to providing outstanding coverage, **PROMAX XRP** offers excellent rust protection while creating a professional, fade resistant finish.

### *Features*

- Excellent rust protection
- Outstanding coverage and gloss
- Great adhesion
- Professional, fade resistant finish
- Multidirectional fan spray
- Use on multiple substrates

### *Typical Properties*

|                              |                        |
|------------------------------|------------------------|
| Container                    | 16 oz. aerosol         |
| VOC                          | 4.24 #/gal (509.3 g/l) |
| MIR                          | < 1.2-1.9              |
| Salt Spray Test – ASTM-B117  | Excellent              |
| QUV Test - % Gloss Retention | Excellent              |

**PROMAX XRP** is available in the following colors:

|                          |                            |                            |
|--------------------------|----------------------------|----------------------------|
| <b>64013 FLAT BLACK</b>  | <b>64063 GUNMETAL GRAY</b> | <b>64113 CREAM</b>         |
| <b>64023 SATIN BLACK</b> | <b>64073 CAMO BROWN</b>    | <b>64123 HUNTER GREEN</b>  |
| <b>64033 GLOSS BLACK</b> | <b>64083 KHAKI</b>         | <b>64133 CAMO GREEN</b>    |
| <b>64043 GLOSS WHITE</b> | <b>64093 CHERRY RED</b>    | <b>64143 SAFETY YELLOW</b> |
| <b>64053 ALUMINUM</b>    | <b>64103 DARK BLUE</b>     | <b>64153 SAFETY ORANGE</b> |

### *Handling and Application*

#### **PREPARATION:**



1. Clean surface thoroughly and dry.
2. Sand surface with 220-320 grit sandpaper.
3. Blow or wipe off dust and re-clean.

#### **MIXING:**



Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

**APPLICATION:**



Apply light “mist” coats, allowing 5-10 minutes between coats.

**NOTE:** If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

**NOTE:** After each use, turn can upside down and spray several seconds to clear spray tip.

**STORAGE:**



**PROMAX XRP** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **PROMAX XRP** is 2 years when stored under normal conditions.

**TECHNICAL CONSULTATION SERVICE**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

**DISCLAIMER:** The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

**SEM Products, Inc.**  
**1685 Overview Dr. Rock Hill SC 29730**  
**Tel: 800/ 831-1122**  
**[www.semproducts.com](http://www.semproducts.com)**