

SEM

39592 METAL BITE FINISHING GLAZE



A Premium Quality Glaze You Can Sink Your Teeth Into!

39592 “bites” into many common substrates to provide shops with needed versatility.

- Pourable
- Prevents Staining
- Seals Repaired Area
- Adheres to Multiple Substrates
- Easy to Sand and Feather-Edge
- Excellent Filling Characteristics





39592 METAL BITE FINISHING GLAZE

39592 METAL BITE FINISHING GLAZE is a two component polyester finishing glaze designed to be applied over body filler, sand scratches and other minor imperfections. **39592** prevents staining when applied over body filler and seals the repair area. **39592** adheres to a variety of substrates, including aluminum, steel, SMC and fiberglass.

CLEAN



3837() SEM SOLVE. The surface must be free of dirt, oil, grease and rust.

SAND



180 grit paper

MIX



Knead container. Mix 2-inch ribbon of cream hardener with golf ball sized quantity of **39592**.

APPLY



Using a spreader, the film build should not exceed 1/8 inch.

CURE



Allow **39592** to dry for approximately 20 minutes.

SAND



180 grit paper

PAINT



Refer to paint manufacturer's instructions to finish the repair.

STORAGE



39592 should be stored between 40-80°F (4-27°C). The shelf life for **39592** is 2 years when stored under normal conditions.

Please refer to **39592 METAL BITE FINISHING GLAZE TECHNICAL DATA SHEET** for additional detailed information.



The Right Choice